



EPE030/042A0V

Part No. 210751

DATASHEET

Rubber profile

ClickLine

▪ Mechanical data

Dimensions in mm (Tolerances acc. to DIN ISO 3302-1 tl. E2)	30 x 42
Material	EPDM
Delivery length	50 m
Weight	0.55 kg / m
Material hardness	65 Shore A
Aluminium rail	AP-5
End cap	EN-C42

▪ General data

Safety edge (assembled)	ELE030/042A0V2
Sensor length (min. /max.)	0.3 m / 6 m (longer on request)
Cable length (min. /max.)	0.5 m / 25 m
Actuating distance / Pre-travel (A / 100mm/s)*	6 mm
Actuating force (A / 100mm/s)*	60 N
Overtravel at 250 N (B1)*	18 mm
Overtravel at 400 N (B2)*	20 mm
Total travel at 600 N (C)*	27 mm
Operating temperature	-10°C to 55°C
Max. temperature range	-30°C to 75°C
Inactive end range with higher forces	20 mm
Switching angle	2 x 45°
Switching cycles	10'000
Degree of protection	IP65
Electrical Capacity	30 V 100 mA
Actuation resist	≤ 500 Ohm
Standards	EN ISO 13856-2 / EN 12978
EC type examination certificate	E 6587 (Suva)

*Acc. to EN ISO 13856-2; Test piece Ø 80 mm; Test location c3; Test speed (A) 100 mm/s; Temp. 20°C

