

XRF-T.2 bk

Part No. 407680

DATASHEET

Transmitter to XRF wireless transmission system

Transmitter with two programmable inputs for safety edges or switches with dark cover

Mechanical data

Dimensions	121 x 50 x 23 mm
Material (housing)	ASA anthracite
Terminals	4, push-in spring connection Conductor cross section 0.25 – 0.75 mm ²
Cable strain relief	Built in (for cable-Ø 3.1 to 5.2 mm)
Weight	75 g

Electrical data

Supply voltage	1x CR2450N Lithium battery (3 V)
Battery life	Up to 1.2 years (type: RENATA)
Inputs	2, programmable for Safety edge (8.2 kOhm) or contact NC / NO < 6 kOhm / > 12 kOhm
Thresholds	< 6 kOhm / > 12 kOhm
Available codes	65'536
Push button	For pairing
Dip-switches (8k2, NO/NC)	2, factory setting: ON, OFF
Display	LED red

In combination with an XRF receiver

Range	100 m at optimum conditions
Reaction time	Typ. 15 ms
Communication	Bidirectional
Operating frequency	868.3 MHz
Radiated power	< 10 dbm / 10 mW
Low battery indication	Acoustic and optical (on the receiver)

Approvals

EN 300 220, EN 301 489
EN ISO 13849-1 (PLd, Cat.3, MTTFd 640 y)

Ambient conditions

Protection category	IP65
Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +80°C
Rel. air humidity	< 95%, non-condensing



Box contents

Transmitter, 1 battery CR2450N, instruction manuals (DE, EN, FR, IT, NL, SV), mounting material

Dimensions

